
BMSpy Documentation

Release 0.0.6

Steven Masfaraud

February 04, 2016

CONTENTS

1 Getting Started	3
1.1 What is BMS for?	3
1.2 Installation	3
2 Development	5
2.1 Release Notes	5
2.2 Roadmap	6
3 Tutorial	7
3.1 Defining a model	7
3.2 Model methods	8
4 Examples	9
5 Reference	11
5.1 Core	11
5.2 Signals	12
5.3 Blocks	13
Python Module Index	17
Index	19

Contents:


GETTING STARTED

1.1 What is BMS for?

BMS stands for “Block Model Simulator”. It helps defining a `DynamicalSystem`, a collection of variables linked by equations or behaviors.

The values of the model's variables are computed by the model and can be displayed of post-treated.

Here is for example the output of an electric motor model:



1.2 Installation

The easy way:

```
pip install bms
```

or, if you are running python3:

```
pip3 install bms
```

Alternatively, you can download the source at: <https://pypi.python.org/pypi/bms/> After extracting, execute:

```
python setup.py install
```

If you are running python3:

```
python3 setup.py install
```

**CHAPTER
TWO**

DEVELOPMENT

BMS is beeing actively developed! Feel free to interact!

Questions and bugs can be reported on github: <https://github.com/masfaraud/BMSpy/issues>

2.1 Release Notes

see also releases on github: <https://github.com/masfaraud/BMSpy/releases>

2.1.1 Version 0.0.6

- Shinx Documentation
- Variables accessible at time value by DynamicSystem method

2.1.2 Version 0.0.5

- Version number standard change
- Model Saving/Loading from file
- New version of model drawing
- Inputs renamed Signals
- Drag & Drop Model drawer

2.1.3 Version 0.04

- Reorganisation into subpackages of blocks and inputs

2.1.4 Version 0.03

- Bug correction for float time step
- Redefinition of number of steps

2.1.5 Version 0.02

- New blocks such as saturation or coulomb
- Bug fixes

2.1.6 Version 0.01

Initial release

2.2 Roadmap

- Implement computation of derivatives at t=0 for inputs
- Implement indicator of convergence when solving at a time step
- Nice model drawing (upgrade existing drag & drop interface)

**CHAPTER
THREE**

TUTORIAL

The DynamicSystem Class is a python class defined by BMS core. It allows to define a complete model containing all the data for simulation.

3.1 Defining a model

3.1.1 Defining the inputs

Inputs are special variable in the model which are not computed. See the [inputs list](Inputs) Here we define a ramp named which name is e

```
e=Ramp('e',1.)
```

3.1.2 Defining Variables

Let's define a variable s which will be the output of a first order block

```
s=bms.Variable('s')
```

3.1.3 Defining Blocks

Let's define this block:

```
from bms.blocks.continuous import ODE
block=ODE(e,s,[1],[1,3])
```

3.1.4 Defining the model

```
te=10# time of end in seconds
ns=2000 # number of time steps
model=bms.DynamicSystem(te,ns,[block])
```

The blocks are given in a list as third argument

3.2 Model methods

3.2.1 Simulating

```
model.Simulate()
```

3.2.2 Plotting variables

```
model.PlotVariables()
```

3.2.3 Accessing values

Values of variables at a given time t is accessible by:

```
ds.VariablesValues(t)
```

The time values vector of a variable is accessible via the values attribute:

```
import matplotlib.pyplot as plt
plt.plot(ds.t,e.values)
plt.plot(ds.t,s.values)
```

**CHAPTER
FOUR**

EXAMPLES

See the project examples folder on github: <https://github.com/masfaraud/BMSpy/tree/master/bms/examples>

REFERENCE

5.1 Core

Core of BMS. All content of this file is imported by bms, and is therefore in bms
This file defines the base of BMS.

class bms.core.**Block** (*inputs*, *outputs*, *max_input_order*, *max_output_order*)

Abstract class of block: this class should not be instanciate directly

InputValues (*it*)

Returns the input values at a given iteration for solving the block outputs

OutputValues (*it*)

class bms.core.**DynamicSystem** (*te*, *ns*, *blocks*=*[]*)

Defines a dynamic system that can simulate itself

Parameters

- **te** – time of simulation's end
- **ns** – number of steps
- **blocks** – (optional) list of blocks defining the model

AddBlock (*block*)

Add the given block to the model and also its input/output variables

CheckModelConsistency ()

Check for model consistency:

- an input variable can't be set as the output of a block
- a variable can't be the output of more than one block

DrawModel ()

PlotVariables (*subplots_variables=None*)

Save (*name_file*)

name_file: name of the file without extension. The extension .bms is added by function

Simulate ()

VariablesValues (*variables*, *t*)

Returns the value of given variables at time t

Parameters

- **variables** – one variable or a list of variables

- **t** – time of evaluation

graph**bms.core.Load**(*file*)
Loads a model from specified file**exception bms.coreModelError**
Bases: exceptions.Exception**args****message****class bms.core.Signal**(*names*)
Bases: *bms.core.Variable*

Abstract class of signal

values**class bms.core.Variable**(*names*='', *initial_values*=[0])
Defines a variable**Parameters names** – Defines full name and short name.If *names* is a string the two names will be identical otherwise *names* should be a tuple of strings (*full_name*,*short_name*)**values**

5.2 Signals

5.2.1 Functions

Collection of mathematical function signals

class bms.signals.functions.Ramp(*name*='Ramp', *amplitude*=1, *delay*=0, *initial_value*=0)
Bases: *bms.core.Signal*Create a ramp such as : $f(t) = (t - \text{delay}) * \text{amplitude} + \text{initial_value}$ **values****class bms.signals.functions.SignalFunction**(*name*, *function*)
Bases: *bms.core.Signal*

User defined function for signal.

Parameters function – a function that will give the time values to the signal**values****class bms.signals.functions.Sinus**(*name*='Sinus', *amplitude*=1, *w*=1, *phase*=0, *initial_value*=0)
Bases: *bms.core.Signal***values****class bms.signals.functions.Step**(*name*='Step', *amplitude*=1, *delay*=0, *initial_value*=0)
Bases: *bms.core.Signal*

Create a Step of amplitude beginning at time delay

values

5.2.2 Signals

WLTP signals

```
class bms.signals.wltp.WLTP1 (name)
    Bases: bms.core.Signal
    WLTP classe 1 cycle Caution! speed in m/s, not in km/h!
    values

class bms.signals.wltp.WLTP2 (name)
    Bases: bms.core.Signal
    WLTP classe 2 cycle Caution! speed in m/s, not in km/h!
    values

class bms.signals.wltp.WLTP3 (name)
    Bases: bms.core.Signal
    WLTP classe 3 cycle Caution! speed in m/s, not in km/h!
    values
```

5.3 Blocks

5.3.1 Continuous Blocks

Collection of continuous blocks

```
class bms.blocks.continuous.Division (input_variable1, input_variable2, output_variable)
    Bases: bms.core.Block
    output=input1/input2

    InputValues (it)
        Returns the input values at a given iteration for solving the block outputs

    LabelBlock ()

    LabelConnections ()

    OutputValues (it)

    Solve (it, ts)

class bms.blocks.continuous.FunctionBlock (input_variable, output_variable, function)
    Bases: bms.core.Block
    output=f(input)

    InputValues (it)
        Returns the input values at a given iteration for solving the block outputs

    LabelBlock ()

    LabelConnections ()

    OutputValues (it)

    Solve (it, ts)
```

```
class bms.blocks.continuous.Gain (input_variable, output_variable, value)
Bases: bms.core.Block
output=value* input
InputValues (it)
    Returns the input values at a given iteration for solving the block outputs
LabelBlock ()
LabelConnections ()
OutputValues (it)
Solve (it, ts)

class bms.blocks.continuous.ODE (input_variable, output_variable, a, b)
Bases: bms.core.Block
a,b are vectors of coefficients such as H, the transfert function of the block, may be written as:
H(p)=(a[i]p**i)/(b[j]p**j) (Einstein sum on i,j) p is Laplace's variable
InputValues (it)
    Returns the input values at a given iteration for solving the block outputs
LabelBlock ()
LabelConnections ()
OutputMatrices (delta_t)
OutputValues (it)
Solve (it, ts)

class bms.blocks.continuous.Product (input_variable1, input_variable2, output_variable)
Bases: bms.core.Block
output=input1*input2
InputValues (it)
    Returns the input values at a given iteration for solving the block outputs
LabelBlock ()
LabelConnections ()
OutputValues (it)
Solve (it, ts)

class bms.blocks.continuous.Subtraction (input_variable1, input_variable2, output_variable)
Bases: bms.core.Block
output=input1-input2
InputValues (it)
    Returns the input values at a given iteration for solving the block outputs
LabelBlock ()
LabelConnections ()
OutputValues (it)
Solve (it, ts)
```

```
class bms.blocks.continuous.Sum(input_variable1, input_variable2, output_variable)
    Bases: bms.core.Block
        output=input1+input2
        InputValues(it)
            Returns the input values at a given iteration for solving the block outputs
        LabelBlock()
        LabelConnections()
        OutputValues(it)
        Solve(it, ts)
```

5.3.2 Non-linear Blocks

Collection of non-linear blocks

```
class bms.blocks.nonlinear.Coulomb(input_variable, speed_variable, output_variable, max_value,
    tolerance=0)
    Bases: bms.core.Block
```

Return coulomb force under condition of speed and sum of forces (input)

```
        InputValues(it)
            Returns the input values at a given iteration for solving the block outputs
        LabelBlock()
        OutputValues(it)
        Solve(it, ts)
```

```
class bms.blocks.nonlinear.DeadZone(input_variable, output_variable, zone_width)
    Bases: bms.core.Block
```

```
        InputValues(it)
            Returns the input values at a given iteration for solving the block outputs
        OutputValues(it)
        Solve(it, ts)
```

```
class bms.blocks.nonlinear.Hysteresis(input_variable, output_variable, zone_width, initial_value)
    Bases: bms.core.Block
```

```
        InputValues(it)
            Returns the input values at a given iteration for solving the block outputs
        OutputValues(it)
        Solve(it, ts)
```

```
class bms.blocks.nonlinear.Saturation(input_variable, output_variable, min_value, max_value)
    Bases: bms.core.Block
```

output=*min_value* if *input* < *min_value* *output*=*max_value* if *input* > *max_value* *output*=*input* if *min_value* < *input* < *max_value*

```
        InputValues(it)
            Returns the input values at a given iteration for solving the block outputs
        LabelBlock()
```

`OutputValues (it)`

`Solve (it, ts)`

b

`bms.blocks`, 13
`bms.blocks.continuous`, 13
`bms.blocks.nonlinear`, 15
`bms.core`, 11
`bms.signals`, 12
`bms.signals.functions`, 12
`bms.signals.wltp`, 13

A

AddBlock() (bms.core.DynamicSystem method), 11
 args (bms.coreModelError attribute), 12

B

Block (class in bms.core), 11
 bms.blocks (module), 13
 bms.blocks.continuous (module), 13
 bms.blocks.nonlinear (module), 15
 bms.core (module), 11
 bms.signals (module), 12
 bms.signals.functions (module), 12
 bms.signals.wltp (module), 13

C

CheckModelConsistency() (bms.core.DynamicSystem method), 11
 Coulomb (class in bms.blocks.nonlinear), 15

D

DeadZone (class in bms.blocks.nonlinear), 15
 Division (class in bms.blocks.continuous), 13
 DrawModel() (bms.core.DynamicSystem method), 11
 DynamicSystem (class in bms.core), 11

F

FunctionBlock (class in bms.blocks.continuous), 13

G

Gain (class in bms.blocks.continuous), 13
 graph (bms.core.DynamicSystem attribute), 12

H

Hysteresis (class in bms.blocks.nonlinear), 15

I

InputValues() (bms.blocks.continuous.Division method), 13
 InputValues() (bms.blocks.continuous.FunctionBlock method), 13
 InputValues() (bms.blocks.continuous.Gain method), 14

InputValues() (bms.blocks.continuous.ODE method), 14
 InputValues() (bms.blocks.continuous.Product method), 14
 InputValues() (bms.blocks.continuous.Subtraction method), 14
 InputValues() (bms.blocks.continuous.Sum method), 15
 InputValues() (bms.blocks.nonlinear.Coulomb method), 15
 InputValues() (bms.blocks.nonlinear.DeadZone method), 15
 InputValues() (bms.blocks.nonlinear.Hysteresis method), 15
 InputValues() (bms.blocks.nonlinear.Saturation method), 15
 InputValues() (bms.core.Block method), 11

L

LabelBlock() (bms.blocks.continuous.Division method), 13
 LabelBlock() (bms.blocks.continuous.FunctionBlock method), 13
 LabelBlock() (bms.blocks.continuous.Gain method), 14
 LabelBlock() (bms.blocks.continuous.ODE method), 14
 LabelBlock() (bms.blocks.continuous.Product method), 14
 LabelBlock() (bms.blocks.continuous.Subtraction method), 14
 LabelBlock() (bms.blocks.continuous.Sum method), 15
 LabelBlock() (bms.blocks.nonlinear.Coulomb method), 15
 LabelBlock() (bms.blocks.nonlinear.Saturation method), 15
 LabelConnections() (bms.blocks.continuous.Division method), 13
 LabelConnections() (bms.blocks.continuous.FunctionBlock method), 13
 LabelConnections() (bms.blocks.continuous.Gain method), 14
 LabelConnections() (bms.blocks.continuous.ODE method), 14
 LabelConnections() (bms.blocks.continuous.Product method), 14

LabelConnections() (bms.blocks.continuous.Subtraction method), 14
LabelConnections() (bms.blocks.continuous.Sum method), 15
Load() (in module bms.core), 12

M

message (bms.coreModelError attribute), 12
ModelError, 12

O

ODE (class in bms.blocks.continuous), 14
OutputMatrices() (bms.blocks.continuous.ODE method), 14
OutputValues() (bms.blocks.continuous.Division method), 13
OutputValues() (bms.blocks.continuous.FunctionBlock method), 13
OutputValues() (bms.blocks.continuous.Gain method), 14
OutputValues() (bms.blocks.continuous.ODE method), 14
OutputValues() (bms.blocks.continuous.Product method), 14
OutputValues() (bms.blocks.continuous.Subtraction method), 14
OutputValues() (bms.blocks.continuous.Sum method), 15
OutputValues() (bms.blocks.nonlinear.Coulomb method), 15
OutputValues() (bms.blocks.nonlinear.DeadZone method), 15
OutputValues() (bms.blocks.nonlinear.Hysteresis method), 15
OutputValues() (bms.blocks.nonlinear.Saturation method), 16
Step (class in bms.signals.functions), 12
Subtraction (class in bms.blocks.continuous), 14
Sum (class in bms.blocks.continuous), 14

V

values (bms.core.Signal attribute), 12
values (bms.core.Variable attribute), 12
values (bms.signals.functions.Ramp attribute), 12
values (bms.signals.functions.SignalFunction attribute), 12
values (bms.signals.functions.Sinus attribute), 12
values (bms.signals.functions.Step attribute), 12
values (bms.signals.wltp.WLTP1 attribute), 13
values (bms.signals.wltp.WLTP2 attribute), 13
values (bms.signals.wltp.WLTP3 attribute), 13
Variable (class in bms.core), 12
VariablesValues() (bms.core.DynamicSystem method), 11

W

WLTP1 (class in bms.signals.wltp), 13
WLTP2 (class in bms.signals.wltp), 13
WLTP3 (class in bms.signals.wltp), 13

P

PlotVariables() (bms.core.DynamicSystem method), 11
Product (class in bms.blocks.continuous), 14

R

Ramp (class in bms.signals.functions), 12

S

Saturation (class in bms.blocks.nonlinear), 15
Save() (bms.core.DynamicSystem method), 11
Signal (class in bms.core), 12
SignalFunction (class in bms.signals.functions), 12
Simulate() (bms.core.DynamicSystem method), 11
Sinus (class in bms.signals.functions), 12
Solve() (bms.blocks.continuous.Division method), 13
Solve() (bms.blocks.continuous.FunctionBlock method), 13
Solve() (bms.blocks.continuous.Gain method), 14
Solve() (bms.blocks.continuous.ODE method), 14
Solve() (bms.blocks.continuous.Product method), 14
Solve() (bms.blocks.continuous.Subtraction method), 14
Solve() (bms.blocks.continuous.Sum method), 15
Solve() (bms.blocks.nonlinear.Coulomb method), 15
Solve() (bms.blocks.nonlinear.DeadZone method), 15
Solve() (bms.blocks.nonlinear.Hysteresis method), 15
Solve() (bms.blocks.nonlinear.Saturation method), 16